

	Tundra-2.9	Tundra-3.9
Physical Pitch	2.97mm/0.12"	3.91mm/0.15"
Pixel Configuration	SMD1415	SMD1921
Pixel Density	112896px/m ²	65536px/m ²
Module Dimension (WxH)	250x250mm / 9.84"x9.84"	
Panel Dimension (WxHxD)	500x500x80mm / 19.68"x19.68"x3.14"	
	500x1000x80mm / 19.68"x19.68"x3.14"	
No. of Module/panel (WxH)	2x2/2x4	
Module Resolution	84x84px	64x64px
Panel Resolution	168x168px	128x128px
	168x336px	128x256px
Panel Material	Die-Cast Aluminum	
Panel Weight	8kg/14kg (17.63lbs/30.86lbs)	
Gray Scale	16bit	
Contrast Ratio	4000:1	
Avg. Power Consumption	64w/panel	
	128w/panel	
Max. Power Consumption	192w/panel	
	384w/panel	
Operating Temp/Humidity	-10°C - 60°C / 10% - 60%	
Storage Temp/Humidity	-30°C - 60°C/ 10% - 60%	
Refresh Rate	7680hz	
Brightness	≥4500nits	
Viewing Angle(H/V)	160°/140°	
Expected Lifetime	100,000hrs	
Max. Stacking/Hanging	20/10	
Service	Front/Rear	
IP Rating (Front/Rear)	IP65/IP54	
Certification	CCC,CE,ETL,RoHS	